

## Technical Details

Tank capacities between 60 to 240 litres.

Constructed entirely of stainless steel (AISI 304).

Tank construction available in AISI 316L or AISI 316Ti.

Automatic shut of heaters at low water level.

Adjustment of the cleaning time & water temperature.

xx02 and xx12 models have a ultrasonic power adjustment feature: 50%, 75%, & 100%.

High efficiency piezoelectric ultrasonic transducers with special ceramics.

Drainage valve.

## Technical Specifications

Model	Control Type	Basket Size (l*w*h) mm	Tank Size (l*w*h) mm	External Size (l*w*h) mm	Tank Capacity lit	Total Power kW
CleanMax-N 6001	Analogue	450*250*350	550*300*400	1200*500*900	60	2,75
CleanMax-N 6002						
CleanMax-N 6011	Digital					
CleanMax-N 6012						
CleanMax-N 8001	Analogue	560*280*350	650*330*400	1300*530*900	80	4,2
CleanMax-N 8002						
CleanMax-N 8011	Digital					
CleanMax-N 8012						
CleanMax-N 12001	Analogue	560*450*350	650*500*400	1300*700*900	120	5,25
CleanMax-N 12002						
CleanMax-N 12011	Digital					
CleanMax-N 12012						
CleanMax-N 16001	Analogue	800*450*350	900*500*400	1550*700*900	160	8,0
CleanMax-N 16002						
CleanMax-N 16011	Digital					
CleanMax-N 16012						
CleanMax-N 24001	Analogue	800*680*350	900*750*400	1550*1050*900	240	10,0
CleanMax-N 24002						
CleanMax-N 24011	Digital					
CleanMax-N 24012						