

## Technical Details

- Pneumatically powered vertical opening front access door.
- Heavy duty stainless steel mesh motor driven component basket.
- Integral fluid filtration system.
- Corrosion resistant spray jets.
- Chemical & corrosion resistant stainless steel pump.
- Microprocessor or PLC controlled.
- Electrical powered fluid heating.
- Optional double skinned fluid tanks with 20mm thick insulation.

## Technical Specifications

Model	Processes	Basket Diameter	Loading Weight	Loading Height	External Size (l*w*h)	Total Power
		mm	kg	mm	mm	kW
SprayClean 90 W	Washing	900	300	500	1550*1400*2050	7,5
SprayClean 120 W	Washing	1200	450	650	1950*1750*2150	15,0
SprayClean 150 W	Washing	1500	600	750	2400*2100*2400	22,5
SprayClean 180 W	Washing	1800	800	900	2700*2400*2600	22,5
SprayClean 90 WR	Washing Rinsing	900	300	500	1550*1900*2050	7,5/7,5
SprayClean 120 WR	Washing Rinsing	1200	450	650	1950*2250*2150	15,0/7,5
SprayClean 150 WR	Washing Rinsing	1500	600	750	3000*2100*2400	22,5/15,0
SprayClean 180 WR	Washing Rinsing	1800	800	900	3300*2400*2600	22,5/15,0
SprayClean 90 WRD	Washing Rinsing Drying	900	300	500	1550*1900*2200	7,5/7,5/11,0
SprayClean 120 WRD	Washing Rinsing Drying	1200	450	650	1950*2250*2300	5,0/7,5/18,0
SprayClean 150 WRD	Washing Rinsing Drying	1500	600	750	3000*2100*2600	22,5/15,0/22,0
SprayClean 180 WRD	Washing Rinsing Drying	1800	800	900	3300*2400*2800	22,5/15,0/33,0